


- 1 GND
- 2 RST
- 3 SW
- 4 SCL
- 5 VDD
- 6 RST
- 7 VDD

PIN	Symbol
1	A
2	K
3	K
4	VCC
5	IOVCC
6	RST
7	TE
8	PWM
9	GND
10	DOP
11	DON
12	GND
13	D1P
14	D1N
15	GND
16	CP
17	CN
18	GND
19	D2P
20	D2N
21	GND
22	D3P
23	D3N
24	GND
25	TPINT
26	TPSDA
27	TPSCL
28	TPRST
29	TPVCC
30	TPVCC

- 基本规格
- 制程: 2024年11月
 - 产品规格: 2024年11月
 - 尺寸: 186.15±0.2mm (W) × 191.28±0.2mm (H)
 - 重量: 1.2g (±0.1g)
 - 背光: 450CD/M2 (MIN), 500CD/M2 (TYP)
 - 功耗: 21V, 80mA
 - 接口: MIPI
 - 其他: 符合RoHS标准

LCD 型号/规格/分辨率	BOE/IPS
背光方向	ALL
背光片	上: 1.5MM / 下: 1.5MM
驱动IC / 类型	FD5893DC
模组厚度 (不含TP)	4.50CD/M2 (MIN), 5.00CD/M2 (TYP)
外观颜色/颜色	X=0.29±0.03, Y=0.30±0.03



REVISED RECORD	
NO.	初版
DATE	2024-11-26
Drawn	
Check	
Approve	
Dwn.No	

深圳市爱普拓思科技有限公司

Page: 1 of 1 Unit: mm Date: 2024-11-26

Rev: V0 Scale: 1/1 Projection:

DBT070BHC30R050A